

## STRONG 40

136-19-303-E

The slim light channel - linear architectural lighting in the smallest of spaces

**Design:** linear  
**wall mounting:** available  
**ceiling mounting:** available  
**recessed mounting:** available  
**surface mounting:** available  
**track mounting:** available  
**material:** aluminum  
**colour:** RAL of choice  
**Width [mm]:** 40  
**Length [mm]:** konfigurierbar  
**Height/depth [mm]:** 75

A multifunctional lighting system for well differentiated as straightforward architectural lighting. With a width of only 40 mm, it is very filigree and can be configured consistently as a surface-mounted, pendant and recessed luminaire for plasterboard ceilings and walls. Lighting situations such as offices, schools or shops with different light and light directions can be implemented.

The technical data relate to a running meter and may have to be adapted to the specific customer length.

**light direction:** direct  
**Luminaire Luminous Flux [lm]:** 2170  
**light cover:** Acryl prismatic  
**light symetry:** symmetrical  
**System efficiency (lm/W):** 99  
**Colour Temperature [K]:** 3000  
**Colour Rendering Index:** >80  
**control:** on/off  
**control gear incl:** 22  
**Nominal voltage:** 230V 0/50/60Hz  
**emergency ready:** yes  
**emergency battey 3h:** included  
**Degree of protection:** IP30  
**Protection class:** I  
**control gear incl:** ja  
**Stand:** 20.05.2022

