

## STRONG 55

153-0013-104-E

The light channel for direct lighting - efficient, versatile and of the highest quality

**Design:** linear  
**wall mounting:** available  
**ceiling mounting:** available  
**recessed mounting:** available  
**surface mounting:** available  
**track mounting:** available  
**colour:** white RAL 9016  
**Width [mm]:** 55  
**Length [mm]:** konfigurierbar  
**Height/depth [mm]:** 80  
**Installation Depth [mm]:** 120

Uniquely slim, uniquely efficient and uniquely versatile, this makes the light line system an all-rounder - and ideal for lighting schools, workplaces and traffic zones.

The technical data relate to a running meter and may have to be adapted to the specific customer length.

**light direction:** direct  
**Luminaire Luminous Flux [lm]:** 3480  
**light cover:** Acryl satined  
**System efficiency (lm/W):** 116  
**Colour Temperature [K]:** 4000  
**Colour Rendering Index:** >80  
**control:** ON/OFF  
**control gear incl:** 30  
**Nominal voltage:** 230V 0/50/60Hz  
**life cycle:** 70.000h (L80/B10)  
**emergency ready:** yes  
**emergency battey 3h:** included  
**Degree of protection:** IP30  
**Protection class:** I  
**control gear incl:** ja  
**Stand:** 11.08.2022

