

VELTO

VEL-4702-22-30

The modern, slim workplace lighting as a floor or pendant luminaire

Design: linear
Design Version: Pendelleuchte
ceiling mounting: available
pendant mounting: available
colour: silber
Width [mm]: 48
Length [mm]: 1285
Height/depth [mm]: 76
suspension length [mm]: 1500
weight net [kg]: 4

With a VELTO, two workplaces can be illuminated in accordance with standards. The light source of this filigree floor luminaire is almost invisible thanks to perfectly glare-free micro-reflectors. This almost eliminates direct glare. With comfortable touch operation as standard and also in the TunableWhite version on request.

Sensors integrated in the luminaire head, daylight and motion sensors can be switched on and off individually, detection range up to 3m, touch control panel, operating device integrated in the standpipe, high stability, cable design variable in wall or ta

Type: LINEAR
light direction: direct/indirect
Luminaire Luminous Flux [lm]: 7430
light cover: Linse linear
light steering: reflector
light symetry: symmetrical
Unified Glare Ratio UGR: 13
System efficiency (lm/W): 110
Colour Temperature [K]: 3000
Colour Rendering Index: >80
control: DALI
control gear incl: 50
Nominal voltage: 230V 0/50/60Hz
life cycle: 50.000h (L80/B10)
Degree of protection: IP40
Protection class: I
control gear incl: yes
Stand: 28.09.2022

